APPENDIX C2 – GENERAL PERMIT NOTES

"DRIVEWAYS AND LOCAL ROADS"

| 1. | THE EXISTING SPEED LIMIT ON | S.R | _IS | _M.P.H. | |
|----|--|--|---|---|--|
| 2. | THE RIGHT-OF-WAY IS | ACCESS | . (LIMITED C | OR FREE) | |
| 3. | 4. PENNDOT PUBLICATION 41, F | WING: , DESIGN MA APPROVED (APPROVED (PRODUCERS PRODUCERS FRAFFIC ENC , STANDARD PAVEMENT OFFICIAL TI B, TEMPORA | ANUAL PAR' AGGREGAT CONSTRUC OF BITUM OF READY GINEERING OS FOR ROA MARKINGS RAFFIC COI | T 2 – HIGHWAY DESIGN E PRODUCERS (BULLETIN 14) TION MATERIALS (BULLETIN 15) INUOUS MATERIALS (BULLETIN 41) '-MIX CONCRETE (BULLETIN 42) MANUAL ADWAY CONSTRUCTION S AND SIGNING STANDARDS NTROL DEVICES | |
| 4. | DETAILS, OTHER THAN THOSE DRAWINGS: (Provide the Roadway Construction) | | | | |
| 5. | THE DRIVEWAY HAS BEEN DES CONSISTENT WITH TITLE 67, CH | | | ONSTRUCTED AND MAINTAINED) ONS. | |
| 6. | PA STATE HIGHWAY RIGHT-OF- | WAY MAY N | OT BE USE | D FOR PARKING. | |
| 7. | PERMITTEE IS RESPONSIBLE FOR FACILITIES AND DRAINAGE. | OR MAINTEN | NANCE OF A | ALL AUTHORIZED STRUCTURES, | |
| 8. | PERMITTEE IS RESPONSIBLE FOR PAVEMENT MARKINGS. | OR MAINTEN | NANCE OF A | ALL AUTHORIZED SIGNS AND | |
| 9. | CONTACT PENNSYLVANIA ONE BEFORE EXCAVATION OR DEM | | | | |
| 10 | ANTICIPATED AVERAGE DAILY | TRAFFIC (AL | OT) FOR TH | E PROPOSED ACCESS IS: | |
| | CARSSINGLE UNIT TRUCKS AN | D COMBINA | TIONS. | | |
| | ANTICIPATED DAILY TRIPS FORCARS | THE PROP | OSED ACCE | ESS IS: | |
| | SINGLE UNIT TRUCKS AN | D COMBINAT | TIONS | | |

| 11 | . DISTANCE TO THE NEAREST INTERSECTION IS: RTLT. | · |
|----|--|---|
| | DISTANCE TO THE NEAREST OPPOSITE DRIVEWAY IS: RTLT. | |
| | DISTANCE TO THE NEAREST ADJACENT DRIVEWAY IS: RTLT. | |
| | · | |
| 12 | .IF A TRAFFIC SIGNAL IS WITHIN 500 FEET OF THE SITE, CALL THE DISTRICT T ENGINEER ATAT LEAST 3 DAYS PRIOR TO THE START OF WOR | |
| 13 | THIS PERMIT MAY BE RESTRICTED ON WORKING HOURS AND TIMES FOR HOWEEKENDS, AND SPECIAL OR UNFORESEEN EVENTS AND WILL REQUIRE APPROMED THE COUNTY OFFICE PRIOR TO WORKING DURING THESE PERIODS. | |

- 14.THE PERMITTEE'S CONTRACTOR SHALL SAWCUT AND REMOVE SHOULDER MATERIAL AS NECESSARY TO ENSURE THE PAVEMENT REPLACEMENT IS ADJACENT TO THE FULL-DEPTH PAVEMENT OF THE TRAVEL LANE.
- 15. FINAL APPROVAL OF THE PROPOSED SAWCUT LOCATION WILL BE AT THE DISCRETION OF THE INSPECTOR-IN-CHARGE AND WILL BE CONFIRMED AT THE PRE-CONSTRUCTION MEETING. IF THE SAWCUT MUST BE LOCATED WITHIN A TRAVEL LANE, IT WILL BE NECESSARY TO MILL AND OVERLAY THE TRAVEL LANE TO PREVENT A JOINT IN A WHEEL PATH.
- 16. THE PROPOSED PAVEMENT SECTION MUST BE AS INDICATED ON THE PLAN, OR MATCH THE EXISTING AS FOUND IN THE FIELD, WHICHEVER IS GREATER.
- 17. PRIOR TO AN OVERLAY, BITUMINOUS OR CONCRETE BASE REPAIR OR JOINT REPLACEMENT MAY BE REQUIRED. REPAIR/REPLACEMENT WILL BE AT THE DISCRETION OF THE INSPECTOR-IN-CHARGE.
- 18. ALL EXISTING PAVEMENT MARKINGS WHICH ARE NO LONGER APPROPRIATE SHALL BE ERADICATED BY THE PERMITTEE. THE PERMITTEE SHALL PLACE ALL REQUIRED NEW PAVEMENT MARKINGS.
- 19. ALL PAVEMENT MARKINGS OTHER THAN LONGITUDINAL LINES TO BE HOT THERMOPLASTIC (PENNDOT PUBLICATION 111, TC-8600).
- 20. MATCH EXISTING PAVEMENT MARKINGS AT THE LIMITS OF WORK.
- 21. MATERIAL CERTIFICATION MUST BE PROVIDED, BY AN APPROVED MANUFACTURER LISTED IN THE DEPARTMENT'S PUBLICATION 35 (BULLETIN 15), FOR ALL MATERIALS AND STRUCTURES WITHIN PENNDOT RIGHT-OF-WAY.
- 22. THE PERMITTEE SHALL CONTACT THE COUNTY MAINTENANCE MANAGER AT THE TIME OF THE GUIDERAIL REMOVAL; ALL EXISTING GUIDERAIL TO BE REMOVED SHALL BE TRANSPORTED TO AND STORED AS PER THE DIRECTION FROM THE COUNTY

MAINTENANCE MANAGER OR HIS REPRESENTATIVE.

- 23. ALL PROPOSED PEDESTRIAN FACILITIES REFLECTED ON THESE PLANS, INCLUDING THOSE THAT ARE OUTSIDE OF PENNDOT LEGAL RIGHT-OF-WAY, SHALL BE CONSTRUCTED TO COMPLY WITH THE REQUIREMENTS OF THE U.S. ACCESS BOARD, PUBLIC RIGHT-OF-WAY ACCESSIBILITY GUIDELINES (PROWAG) OF THE ACCESSIBILITY GUIDELINES OF BUILDINGS AND FACILITIES (ADAAG). PENNDOT DESIGN MANUAL PART 2, CHAPTER 6, AND PENNDOT STANDARDS FOR ROADWAY CONSTRUCTION (PENNDOT PUBLICATION 72M, RC-67M) PROVIDE GUIDANCE ON ADA ACCESSIBLE DESIGN FOR PEDESTRIAN FACILITIES AND CAN BE UTILIZED FOR REFERENCE.
- 24. ALL SLOPE MEASUREMENTS WILL BE INSPECTED/VERIFIED WITH A 2-FOOT SMART LEVEL.
- 25. IT IS THE RESPONSIBILITY OF THE PERMITTEE TO REMOVE ANY DEBRIS AND FLUSH OUT ALL EXISTING AND NEW STORM DRAINAGE FACILITIES WITHIN THE PROJECT LIMITS AT THE COMPLETION OF THE CONSTRUCTION.
- 26. MODIFICAITONS TO EXISTING DRAINAGE STRUCTURES MAY RESULT IN THE NEED TO REPLACE THE STRUCTURE. REPLACEMENT WILL BE AT THE DISCRETION OF THE INSPECTOR-IN-CHARGE.
- 27. STRUCTURAL STEEL BICYCLE SAFE GRATES MUST BE PROVIDED FOR ALL INLETS WITHIN THE ROADWAY PAVEMENT OF THOSE THAT MAY RECEIVE BICYCLE TRAFFIC (PENNDOT PUBLICATION 72M, RC-45M).
- 28. THE RESPONSIBILITY FOR ENSURING THAT ALL UTILITY POLES WITHIN THE PROPOSED PAVING ARE RELOCATED OUTSIDE OF PAVED AREAS AND SHOULDERS SHALL BE THAT OF THE PERMITTEE. THE UTILITY POLES MUST BE RELOCATED BEFORE THE START OF ANY PAVING OPERATIONS.
- 29. THE PERMITTEE IS RESPONSIBLE FOR THE COORDINATION OF RELOCATING ANY CONFLICTING UTILITIES WHICH ARE A RESULT OF THESE IMPROVEMENTS.
- 30. ALL UTILITY RELOCATION PERMITS TAKE PRECEDENCE OVER THE UTILITY RELOCATION POSITIONS SHOWN ON THE HOP PLANS.
- 31. (Provide a List of Public Utilities in accordance with Act 287-1974. List the name, address with Zip Code, and the name, title, and telephone number of the appropriate utility representative.)
- 32.(A note referencing the specific PennDOT plan of record, road docket, or other basis of PennDOT Legal Right-of-Way width must be provided on the plans. Refer to PennDOT Publication 14M, Chapter 2 for example notes.)

MAINTENANCE AND PROTECTION OF TRAFFIC (MPT) NOTES

- THIS WORK CONSISTS OF THE MAINTENANCE AND PROTECTION OF TRAFFIC AND THE PROTECTION OF THE PUBLIC WHEN APPROACHING AND DEPARTING THE CONSTRUCTION AREA AND WITHIN THE LIMITS OF CONSTRUCTION.
- 2. FURNISH, ERECT, PLACE AND MAINTAIN TRAFFIC CONTROL SIGNS AND DEVICES.
 MAINTAIN TRAFFIC DURING HOURS OF CONSTRUCTION AND AT ALL OTHER TIMES
 CONSISTENT WITH THE METHODS INDICATED ON THESE DRAWINGS AND THE
 FOLLOWING:
 - 1. PENNDOT PUBLICATION 35;
 - 2. PENNDOT PUBLICATION 46;
 - 3. PENNDOT PUBLICATION 72M;
 - 4. PENNDOT PUBLICATION 111;
 - 5. PENNDOT PUBLICATION 212;
 - 6. PENNDOT PUBLICATION 213;
 - 7. PENNDOT PUBLICATION 236;
 - 8. PENNDOT PUBLICATION 408; AND
 - 9. MUTCD, CURRENT EDITION.
- 3. REMOVE THESE DEVICES IMMEDIATELY UPON COMPLETION OF THE WORK. PENNDOT WILL REMOVE ANY TRAFFIC CONTROL DEVICES ERECTED BY DEPARTMENT FORCES.
- PERMITTEE MUST ARRANGE FOR INSPECTION OF ALL TRAFFIC CONTROL DEVICES PRIOR TO START OF WORK.
- 5. COVER OR REMOVE ALL CONFLICTING SIGNS AND ERADICATE ALL CONFLICTING PAVEMENT MARKINGS.
- 6. MOUNT ALL LONG-TERM ADVANCE WARNING SIGNS ON TYPE III BARRICADES UNLESS OTHERWISE NOTED OR INSTRUCTED BY DISTRICT OFFICE.
- 7. ALL SIGNS AND DEVICES TO BE MAINTAINED IN NEW OR LIKE NEW CONDITION.
- 8. DRIVEWAYS WILL BE KEPT ACCESSIBLE AT ALL TIMES. LOCATE ALL SIGNS SO THAT SIGHT DISTANCES WILL NOT BE OBSTRUCTED AT DRIVEWAYS AND LOCAL ROADS.
- 9. ALL CHANNELIZING DEVICES, BARRICADES, AND SIGNS SHALL HAVE TYPE III OR BETTER PRISMATIC RETROREFLECTIVE SHEETING. SHEETING SHALL BE APPROVED AND LISTED IN PENNDOT PUBLICATION 35 (BULLETIN 15).
- 10.NO TRAFFIC RESTRICTIONS OR LANE CLOSURES ARE PERMITTED BETWEEN 6:00 AM AND 9:00 AM AND BETWEEN 3:00 PM AND 6:00 PM MONDAYS THROUGH FRIDAYS OR ON LEGAL HOLIDAYS AND WEEKENDS ASSOCIATED WITH LEGAL HOLIDAYS. ALL RESTRICTIONS AND CLOSURES ARE TO BE REMOVED BY NOON ON THE DAY PRIOR TO THE LEGAL HOLIDAY.

- 11. PERMITTEE SHALL NOTIFY LOCAL EMERGENCY AUTHORITIES (E.G., POLICE, FIRE, MEDICAL), AFFECTED BUSINESSES, SCHOOL DISTRICT(S), THE GENERAL PUBLIC, THE DISTRICT PERMIT MANAGER AND THE DISTRICT APRAS COORDINATOR AT LEAST FOURTEEN DAYS PRIOR TO ANY SIGNIFICANT TRAFFIC IMPACTS (E.G., LATERAL WIDTH RESTRICTIONS LESS THAN 16 FEET, DETOURS).
- 12. MAINTENANCE AND PROTECTION OF TRAFFIC DURING CONSTRUCTION SHALL BE IN ACCORDANCE WITH APPLICABLE PATA DRAWING (S)______IN THE CURRENT PENNDOT PUBLICATION 213, "TERMPORARY TRAFFIC CONTROL GUIDELINES".
- 13. DROPOFFS CREATED BY CONSTRUCTION OPERATIONS SHALL BE TREATED CONSISTENT WITH PUBLICATION 408, SECTION 901.3(J).
- 14. REMOVE ALL SHORT-TERM WORK ZONE TRAFFIC CONTROL SIGNING UPON COMPLETION OF THAT DAY'S WORK PERIOD.
- 15. RESTRICTING TRAFFIC FLOW WITHIN THE WORK AREA SHALL BE MINIMIZED TO PREVENT TRAFFIC CONGESTION AND UNSAFE TRAFFIC CONDITIONS.
- 16. NOTIFY THE LOCAL MUNICIPALITY WHERE SIGNALIZED INTERSECTIONS FALL WITHIN THE WORK ZONE. DO NOT FLAG A SIGNALIZED INTERSECTION WITHOUT THE MUNICIPALITY PLACING THE SIGNAL ON FLASH.
- 17. THE CONTRACTOR SHALL COMPLY WITH ACT 229 OF DECEMBER 2002 DURING CONSTRUCTION ACTIVITIES WITHIN PENNDOT'S RIGHT-OF-WAY.

This Is The Desired Format For The General Permit Notes and MPT Notes.

Please Include These On First Plan Sheet.

This Section Will Differ Based on Individual Situation.

Please Add Any Additional Notes That Apply.